




hot water trailers

trail jet 15 300-24-70-d	500-15-100-d	trail jet 30 500-30-100-d	300/500 bar
100 - 300 bar	100 - 500 bar	100 - 500 bar	
13 - 24 l/min	8 - 15 l/min	17 - 30 l/min	30 m, DN10
30 - 70° C (100° C)	30 - 100° C	30 - 100° C	
99 kW 12 v dc	99 kW 12 v dc	198 kW 12 v DC	20 m, DN10
4,5 l/h heating oil	4,5 l/h heating oil	9,0 l/h heating oil	
23 kW / 15 kW 1900 rpm, 1000 rpm, 2 cyl., 1370 ccm, oil	23 kW / 15 kW 1900 rpm, 1000 rpm, 2 cyl., 1370 ccm, oil	36,4 kW / 33 kW 2100 rpm, 1000 rpm, 4 cyl., 3620 ccm, oil	
2,4 l/h diesel	2,4 l/h diesel	4,2 l/h diesel	
15 kW 1450 rpm, 1,0 - 8,0 bar, 40° C	15 kW 1450 rpm, 1,0 - 8,0 bar, 40° C	30 kW 1050 rpm, 2,0 - 8,0 bar, 40° C	
060 USgal/min	030 USgal/min	055 USgal/min	
■	■	■	
■	■	■	
■	■	■	
24 h	24 h	24 h	
24 months	24 months	24 months	
200 l	200 l	400 l	
90 l	90 l	70 l / 150 l	
900 kg, 100 kg	900 kg, 100 kg	1430 kg, 100 kg	
3200 x 1600 x 1830 mm	3690 x 1600 x 1830 mm	3690 x 1980 x 2050 mm	
LpA = 76 dB LWA = 99 dB	LpA = 76 dB LWA = 99 dB	LpA = 75 dB LWA = 99 dB	
g577	g576	g572	

perfect jobs by perfect accessories



cold water trailers

trail jet 30 500-30-0-d	1000-14-0-d	trail jet 125 1000-65-0-d	9250-26-0-d	3000-22-0-d
100 - 500 bar	100 - 1000 bar	300 - 1000 bar	600 - 2500 bar	600 - 3000 bar
17 - 30 l/min	8 - 13 l/min	29 - 65 l/min	11 - 26 l/min	10 - 22 l/min
36, 4 kW / 31 kW , 1800 rpm, 1000 rpm, 4 cyl., 4760 ccm, 3620 ccm, oil	36, 4 kW / 31 kW , 1800 rpm, 1000 rpm, 4 cyl., 4760 ccm, 3620 ccm, oil	129 kW / 125 kW 2300 rpm, 1000 rpm, 4 cyl., 4760 ccm, water	129 kW / 125 kW 2300 rpm, 1000 rpm, 4 cyl., 4760 ccm, water	129 kW / 125 kW 2300 rpm, 1000 rpm, 4 cyl., 4760 ccm, water
4,3 l/h, diesel	4,3 l/h, diesel	18,5 l/h, diesel	18,5 l/h, diesel	18,5 l/h, diesel
28 kW 1030 rpm, 2,0 - 8,0 bar, 40° C	28 kW 1030 rpm, 2,0 - 8,0 bar, 40° C	125 kW / 600 rpm, 2,0 - 8,0 bar, 40° C	125 kW / 600 rpm, 2,0 - 8,0 bar, 40° C	125 kW / 600 rpm, 2,0 - 8,0 bar, 40° C
055 USgal/min	019 USgal/min	090 USgal/min	023 USgal/min	018 USgal/min
■	■	■	■	■
■	■	■	■	■
24 h	24 h	24 h	24 h	24 h
24 months	24 months	24 months	24 months	24 months
200 l	200 l	400 l	400 l	400 l
90 l	90 l	210 l	210 l	210 l
900 kg, 100 kg	900 kg, 100 kg	1980 kg, 100 kg	1980 kg, 100 kg	1980 kg, 100 kg
3200 x 1600 x 1700 mm	3200 x 1600 x 1700 mm	3730 x 1980 x 2025 mm	3730 x 1980 x 2025 mm	3730 x 1980 x 2025 mm
LpA = 76 dB LWA = 99 dB	LpA = 76 dB LWA = 99 dB	LpA = 93 dB LWA = 115 dB	LpA = 93 dB LWA = 115 dB	LpA = 93 dB LWA = 115 dB
g516	g360	g555	g556	g574

services



top rent



project press



super service







Falch gmbh
headquarter
street of water jetting 1
89143 blaubeuren-seissen (germany)

☎ +49 7344 9244-0 ✉ info@falch.com
☎ +49 7344 9244-4090 🌐 www.falch.com

trailers
falch worldwide number 1
in water jetting trailers!



special features



stainless steel heaters



fuel tank filters



2 water filter system



2-lance operation



tandem operation



burner bypass system



protected connections



water softener oil storage

only 2 chassis for all of your projects!

hot water trailers



trail jet 15
500-15-100-d
15 kW, 500 bar, 15 l/min, 100° C

trail jet 30
500-30-100-d
30 kW, 500 bar, 30 l/min, 100° C

trail jet 15
300-24-70-d
15 kW, 300 bar, 24 l/min, 70° C

cold water trailers



trail jet 30
1000-13-0-d
30 kW, 1000 bar, 13 l/min

trail jet 30
500-30-0-d
30 kW, 500 bar, 30 l/min

trail jet 125
1000-65-0-d
125 kW, 1000 bar, 65 l/min

trail jet 125
2500-26-0-d
125 kW, 2500 bar, 26 l/min

trail jet 125
3000-22-0-d
125 kW, 3000 bar, 22 l/min



protective frame of steel noise insulation storage box unbreakable fenders zink coated chassis water + fuel tanks falch order system falch order system bench vise anti freeze system easy control radio control cable control